

QINGDAO MAGIC ANDY HARDWARE CO.,LTD

Add: RM1621, B(north) building, No.63 Haier road, Qingdao, China
Tel: 0086-532-80999608 80999626 80999627 80999629
Fax:0086-532-80999609 Mobile:0086-013708996523
E-mail: sales@cnmagicandy.com manager@cnmagicandy.com
HTTP://www.cnmagicandy.com

QINGDAO MAGICANDY HARDWARE CO.,LTD

PLASTIC PRODUCTS



COMPANY PROFILE

QINGDAO MAGICANDY HARDWARE CO.,LTD

leading enterprise in the field of nationwide PVC reinforced hose examined and approved by China Plastics processing industry Association, and it is the largest manufacturer of plastic and rubber series in China. The company, equipped with advanced production equipments and complete quality testing facilities, covering an area of 87,000 square meters and 35000 square meters of modernized standard workshops with 120 specialized production lines which have the annual production capacity of 60,000tons, owning the right of dealing with import and export business.

With strong technical force and powerful products innovating capacities, the company processes more than 40 national patent, and won the quality, environmental and Occupational Health and Safety of three System Certification. All the products used for foodstuffs have been tested by the Swiss SGS according to the American FDA Standard, and meet all the regulations of contacting with foods. The company obtained the health permit approval document for products related to health and safety of drinking water issued by the Department of Health of Shandong. The company has been awarded "AAA Grade Credit Enterprise" by CPPIA.

Main products: PVC garden hose, PVC fiber reinforced hose, PVC transparent soft hose, PVC spiral steel wire reinforced, PVC/PVC&Rubber mixed air hose. PVC suction hose, fire hose, PVC Layflat hose, and soaker hose, (various layers, different color).

Since built from 1990s, we learned good skill to cooperate with our customers from different markets.

Based on the principle of "suitable quality, high service, and high efficiency", we do hope to build business relation with you to achieve the mutual benefit.







GRARDEN HOSE

01-02 PVC Grarden Hose
03-04 Eva Grarden Hose

05 Expandable Hose

06 Soaker Hose

07

08

11-12

13

Clear Vinyl Hose

PVC Braided Hose

03 IRRIGATE HOSE

14 Fire Hose

15-16 PVC Layflat Hose

17-18 PVC Suction Hose

19 PVC Steel Wire

Reinforced Hose

PVC Fiber & Steel

Wire Reinforced Hose

2 AIR HOSE

09-10 Industrial Air Hose

PVC Duplex Hose

High Pressure Spray Hose

04 HOSE FITTINGS

21-22 Spary Gun

20

24

31

Water Wands

Sprinkler

25 Hose Cart & Reel

26-30 Hose Connector

Cam And Groove Couplings



Eco-friendly Material



and Cold





Resistance



PVC GARDEN HOSE



ECONOMIC DUTY: 3 LAYER

- 1> Inner Layer In Algae-Proof PVC
- 2> Braid In Polyester
- 3> Outer Layer In Uv Ray-Proof PVC



HEAVY DUTY: 4 LAYER

- 1> Inner Layer In Algae-Proof PVC
- 2> Braid In Polyester
- 3> Middle Layer In PVC
- 4> Outer Layer In Uv Ray-Proof PVC.
- Barium, Cadmium And Lead Free



PVC NON-TORSION HOSE

1> Inner Layer In Algae-Proof PVC 2> Braid In Polyester(Special Crochet Process), Due To Its Unique Structure, This Hose Possess Some Special Advantages, Such As Non-Torsion, Non-Twist. So The Water And Other Liquid Can Go Through It More Smoothly

3> Outer Layer In Uv Ray-Proof PVC



LENGTH

10m to 50m Popular sizes: 15m 20m 25m 50m 25 to 100feet Popular sizes: 25' 50' 75' 100'

COLOR

Green, Yellow, Blue, Red, Orange, etc

PACKAGE

Be able to pack with shrink flim + Color label + Carton or as per buyer's request

MOQ

Mixed 1x20' container / 5000m per size

APPLICATIONS:

Applicable To All Kinds Of Landscape Water, Vehicle Washing And Clearing, Community And Family, Is A Good Hose Conveying Air, Water, Oil And Other Liquid, Gas.

WORKING TEMPERATURE:

From -5 $^{\circ}$ C To + 65 $^{\circ}$ C

CHARACTERISTIC:

High Pressure Resistance, No Leakage Anti-Abrasion, Anti- Uv, Long Working Life Non-Toxic, Without Odor Lightweight And Flexible, Easy To Coil







With American Style **Brass Coupling**





HOSE KITS Contains 4 Pcs Of Hose Connectors

The regular specification of PVC garden hose

Item No.	Hose Nominal	Size(mm)	Pressure(bar)		
	Dimension(inch)	I.D.	O.D.	W.P	B.P	
GDGH1216	1/2"	12	16	4	12	
GDGH1621	5/8"	16	21	4	12	
GDGH1925	3/4"	19	25	4	12	
GDGH2531	1	25	31	4	12	



3/8"x50ft EVA Recoil Garden Hose With 3/4 Inch Brass Connectors & 7 Function Spray Nozzle













EVA GARDEN HOSE



3/8"x50ft EVA Recoil Garden Hose
With 3/4 Inch Brass Connectors & Handle

APPLICATIONS:

Widely Used In Irrigating Plants And Washing Cars/Pets, Ideal For Outdoors, Gardens, Yards, Lawns, Greenhouses, Flowerbeds, And Etc.

WORKING TEMPERATURE:

From -5 $^{\circ}$ C To + 65 $^{\circ}$ C

CHARACTERISTIC:

Lightweight,Yet Strong And Durable And Uv-Resistant Eva Construction And Coiled Design, Kink-Free, Tangle-Free, Hassle-Free,Effortless Handling, Ultimate Recoil Memory Is A Great Feature That Makes It Easy & Convenient To Handle And Storage, Highly Elastic, Retractable, Excellent Corrosion Resistant And Durable, Non-Toxic.



GDEVA-C3850

3/8"x50ft EVA Recoil Garden Hose W/Plastic Coupling & 7 Function Spray Nozzle



GDEVA-1001

EVA Recoil Garden Hose W/Plastic Coupling & 5" Nozzle



GDEVA-1002

EVA Recoil Garden Hose
W/Plastic Coupling
& 4 Function Spray Nozzle



10m to 50m Popular sizes: 15m 20m 25m 50m 25 to 100feet Popular sizes: 25' 50' 75' 100'

COLOR

Green, pink, Yellow, Blue, Red, Orange, etc

PACKAGE

Be able to pack with Color box or Blister or Card tied or as per buyer's request









GDEVA-D3850

3/8"x50ft EVA Recoil Garden Hose With Nickel Plated Brass Fittings, & ON/OFF Valve

EXPANDABLE HOSE

APPLICATIONS:

The Product Is Used Watering Lawn, Yard, Garden, Car Washing, Pet Cleaning

WORKING TEMPERATURE:

From -5 $^{\circ}$ C To + 65 $^{\circ}$ C

CHARACTERISTIC:

When The Water Is In, It Can Automatically Expand To Three Times Its Original Length, And When The Water Is Empty, It Can Automatically Shrink To Its Original Length.



COMMON EXPANDABLE HOSE



EXPANDABLE BUNGEE HOSE



COLOR

Green, pink, Yellow, Blue, Red, Orange, etc

PACKAGE

Be able to pack with Color box Card tied or as per buyer's request

The regular specification of common expandable hose								
Item No.	Inner Tube	nner TubeSize(mm) TubeLen		ngth(ft)	Pressu W.P	ssure(bar)		
GDEX0625H	6	9	8	25	0.8-5	10		
GDEX0650H	6	9	15	50	0.8-5	10		
GDEX0675H	6	9	25	75	0.8-5	10		
GDEX06100H	6	9	33	100	0.8-5	10		
GDEX06125H	6	9	40	125	0.8-5	10		
GDEX06150H	6	9	50	150	0.8-5	10		

The regular specif	ication of co	mmon expai	ndable hose	!		
Itama Na	Inner Tub	eSize(mm)	TubeLer	ngth(ft)	Pressu	ıre(bar)
Item No.	I.D.	O.D.	Before	After	W.P	B.P
GDEX0625	6.1	.9.3	8	25	5-8	18
GDEX0650	6.1	.9.3	15	50	5-8	18
GDEX0675	6.1	.9.3	25	75	5-8	18
GDEX06100	6.1	.9.3	33	100	5-8	18
GDEX06125	6.1	.9.3	40	125	5-8	18
GDEX06150	6.1	.9.3	50	150	5-8	18

SOAKER HOSE



3/8 1/2 5/8" Soaker Hose For Garden Beds,
Optional Length 10 25 50 75 ft, Rubber Material



1/2" Flat Soaker Hose for Garden Beds, Optional Length 10 25 50 75 ft,









co-friendly Material



Resistance To Heat and Cold



Wear-Resisting

isting



Anti-Bending

COLOR

Green, Blue, Black, etc

PACKAGE

Be able to pack with Color Sleeve, Color Box, Card tied or as per buyer's request

Clear Vinyl HOSE

















Beautiful.

APPLICATIONS:

Building And Family.

From -5°C To + 65°C

CHARACTERISTIC:

WORKING TEMPERATURE:

It Is Flexible, Durable, Non-Toxic Without Odor, Anti-Erosion And Adaptable To High Pressure Condition. By Adding Colorful Symbol Lines On The Surface Of The Hose. It Looks More

The Product Is Used For Conveying Water, Oil, Gas Under Normal Working Condition In The Factories, Farm, Ship,





PVC BRAIDED HOSE











Wear-Resisting



The regular specification of PVC clear hose & fiber braided soft hose

	Item No.	Hose Nominal	Size(mm)	Pressure(bar)		
	item No.	Dimension(inch)	I.D.	O.D.	W.P	B.P	
	GDRH1014	3/8	10	14	4	12	
	GDRH1216	1/2	12	16	4	12	
	GDRH1519	5/8	15	19	4	12	
	GDRH1924	3/4	19	24	4	12	
	GDRH2530	1	25	30	4	12	
	GDRH3238	1-1/4	32	38	4	12	
	GDRH3845	1-1/2	38	45	4	12	
	GDRH5059	2	50	59	4	12	





PVC Reingorced Hose

APPLICATIONS:

The Product Is Used For Conveying Water Oil, Gas Under Normal Working Condition In The Factory Farm Ship Building And Family.

WORKING TEMPERATURE:

From -5 $^{\circ}$ C To + 65 $^{\circ}$ C

CHARACTERISTIC:

It Is Flexible, Transparent, Durable, Non-Toxic, Without Odor Anti-Erosion And Adaptable To High Pressure Condition. By Adding Colorful Symbol Lines On The Surface Of The Hose, It Looks More Beautiful.

LENGTH

10m to 100m Popular sizes: 15m 20m 25m 50m 25 to 300feet Popular sizes: 25' 50' 75' 100'

COLOR

Green, Yellow, Blue, Red, Orange, etc

PACKAGE

Be able to pack with shrink flim + Color label + Carton or as per buyer's request

MOQ

Mixed 1x20' container / 5000m per size
















INDUSTRIAL AIR HOSE



• Popular sizes: 1/4"x 10ft 1/4"x 15ft 1/4"x 25ft 1/4"x 50ft 1/4"x 100ft

• Popular sizes: 5mmx8mmx 50ft 5mmx8mmx 100ft

8.5mmx12mm 50ft

8.5mmx12mm 100ft

PU Reinforced Hose The Tube Passes Rosh, SGS Cretificate.

Pu braided hose, double brass 1/4" npt fittings, Flexible, high working pressure, no kink or twist, Suitalbe for both indoor & outdoor use.

The tube shows perfect softening property, Which helps to simple use. With the high-strength Polyester fiber inside, based on the high working Pressure which is 2-3 times than the regular Pu tubes and a wide operating temperature range, The tube is suitable for the high reliability fields.



Polyurethane Recoil Air Hose



Polyurethane Air Hose



PVC Reinforced Hose

• Popular sizes: 1/4"x 25ft / 50ft /100ft



Rubber Air Hose

• Popular sizes:

1/4"x 25ft / 50ft with 1/4" MPT brass couping 3/8"x 25ft / 50ft with 1/4" MPT brass couping 1/2"x 25ft / 50ft with 1/2" MPT brass couping




PVC Mixed Rubber Air Hose

1/2"x 10ft / 25ft / 50ft

With 3/8" Industrial Quick Coupler and Plug

PVC OXYGEN & ACETYLENE DUPLEX HOSE





APPLICATIONS:

Being widely used in welding machine, Architecture and lacquer factory.

WORKING TEMPERATURE:

From -5 $^{\circ}$ C To + 65 $^{\circ}$ C

CHARACTERISTIC:

Two Tubes Welder Together, Light, Elastic, Easy To Handle, Anti-Erosion, Resistant To Fire & Easy To Distinguish Due To The Different Colors Of The Tube.






















Oxy Acetylene Welding Hose3/8" B Fittings + Strain Relief Set



Oxygen Acetylene Welder Tool Kit



The regular specification of industrial air hose

Hose Nominal	Size(m	m)	Length	\	Pressur V.P.	, ,	B.P.	Weight
Dimension (inch)	I.D.	O.D.	(m)	Oxygen	Acetylene	Oxygen	Acetylene	(kg/roll)
1/5	5	11.6	50	2.0	1.0	6.0	3.0	11.7
1/4	6.3	13	50	2.0	1.0	6.0	3.0	13.7
5/16	8	15	30	2.0	1.0	6.0	3.0	10.3
3/8	10	17	30	2.0	1.0	6.0	3.0	12.1
1/2	13	20	30	2.0	1.0	6.0	3.0	14.8

HIGH PRESSURE **SPRAY HOSE**

APPLICATIONS:

PVC High Pressure Spray Hose Widely Used For Spraying Chemical of Farmland, Orchards And Vinyl Plastic Greenhous

And Construction.

WORKING TEMPERATURE:

From -5 $^{\circ}$ C To + 65 $^{\circ}$ C

CHARACTERISTIC:

PVC High Pressure Spray Hose Is Strong and Flexible, The weight is 30% Light Than Normal Rubber Hose











UV Resistance

The regular specification of high pressure spray hose

Item No.	Size(m	m)	Thickness	Length	Pressure(Bar)		
item No.	I.D.	O.D.	(mm)	(m)	W.P	B.P	
GD-SHP65	HP65 6.5 12		2.75	50-100	6.0	3.0	
GD-SHP75	7.5	13	2.75	50-100	6.0	3.0	
GD-SHP85	8.5	14	2.75	50-100	6.0	3.0	
GD-SHP100	10	16	3.00	50-100	6.0	3.0	
GD-SHP125	12.5	19	3.25	50-100	6.0	3.0	

FIRE HOSE

APPLICATIONS:

The Shell Uses The Good Quality Fiber, And The Inner Part Uses Good PVC Which Is Anti-High Temperature, Anti High Pressure And Anti-Aging. It Is Used In Line Of Fire Fighting, Irrig-Ation, And Construction.





CHARACTERISTIC: The Regular Size: 1"X20M 2"X20M 3"X20M 4"X20M (Max Length 50M) Reinforcement: PVC Or TPU Color: Clear, Red Or Blue Etc W.P.: 8bars, 10 Bars, 13 Bars And 16Bars Package: Pp Bag Or Carton, As Per Buyer'S Request
















The outer polyester material is more wear-resistant and more eye-catching

Internal high quality PVC or PU coating effectively ensures smooth water flow

















PVC LAYFLAT HOSE

APPLICATIONS:


Suitable For Conveying Liquid Materials In Industry, Agriculture Irrgation, Mines And civil Engine-Ering.

WORKING TEMPERATURE:

From -15 $^{\circ}$ C To + 75 $^{\circ}$ C

CHARACTERISTIC:

Choosing High Strength Polyester Filament And High Quality PVC, It Is Successively Winded, Parted The Threads Regularly And Molded By Plastic Coated Once. With An Attractive Appearance, Soft Surface And Light Weight, High Burst Pressure And Long Service Life, The Product Is Acid & Alkali Resistant, Aging Resistant, Stretching Resistant, Anti-Wrinkle, Non-Toxic, Flavorless And Environmental Protection.







SUPER LIGHT DUTY (2/3BAR)

			_	-
Hose Nominal	Size I.D.	MAX.W.P.	MAX.B.P.	Weight
Dimension (inch)	(mm)	(bar at	(g/metre)	
2	51	2	8	190
3	76	2	8	280
4	103	2	8	430
2	51	3	9	205
3	76	3	9	320
4	103	3	9	490

COMMON LIGHT DUTY (4BAR)

					-
Hose Nominal Dimension	Size I.D.	Thickness	MAX. W.P.	MAX. B.P.	Weight
(inch)	(mm)	(mm)	(bar at 23°C)		(g/metre)
1	25	1.3	4	15	150
1-1/4	32	1.2	4	15	170
1-1/2	38	1.2	4	15	190
2	51	1	4	12	220
2.5	64	1.1	4	12	300
3	76	1.1	4	12	360
4	103	1.25	4	12	550
5	127	1.35	3.5	10	750
6	153	1.35	3	9	900
8	203	2	3	9	1600
10	255	2.4	2.5	7	2600
12	305	2.35	2	6	3000
14	358	3	2	6	500
16	408	3	2	6	6000

MEDIUM DUTY (6BAR)

Hose Nominal Dimension	Size I.D.	Thickness	MAX. W.P.	MAX. B.P.	Weight
(inch)	(mm)	(mm)	(bar at	t 23℃)	(g/metre)
3/4	20	1.35	7	21	110
1	25	1.3	7	21	160
1-1/4	32	1.2	7	21	190
1-1/2	38	1.2	7	21	220
1-1/2	40	1.4	6	18	225
2	51	1.35	6	18	300
2.5	64	1.55	6	18	430
3	76	1.5	6	18	500
4	103	1.9	6	18	800
5	127	2	6	18	1080
6	153	2.4	6	18	1600
8	203	2.6	5	15	2200

HEAVY DUTY (8/10BAR)

Hose Nominal Dimension	Size I.D.	Thickness	MAX. W.P.	MAX. B.P.	Weight
(inch)	(mm)	(mm)	(bar at	23℃)	(g/metre)
3/4	20	1.55	10	30	140
1	25	1.8	10	30	200
1-1/4	32	1.5	10	30	210
1-1/2	38	1.7	10	30	290
1-1/2	40	1.9	10	30	300
1-3/4	45	2	10	30	350
2	51	1.55	8	24	350
2	51	1.8	10	30	420
2.5	64	1.9	10	30	700
3	76	2	8	24	660
3	76	2.55	10	30	850
4	103	2.25	8	24	1000
4	103	2.7	10	30	1200
6	153	3	8	24	2000
8	203	3.2	8	18	2800













PVC SUCTION HOSE

APPLICATIONS:

Widely Used Throughout Industry In Both Positive And Negative Pressure Applications, Ideally For Conveying And Suction Of Water, Oil, Powder, Granules In Pump Industries, Constructions, Mining Industries, Chemical Factories And Many Other Industry Applications.

The regular specification of PVC suction hose



11					
Hose Nominal	- SIZE		MAX.	MAX.	Weight
Dimension (inch)	I.D. (mm)	O.D. (mm)	W.P. (bar at	B.P. : 23℃)	(g/metre)
3/4	19	25	8	24	280
1	25	31	8	24	350
1-1/4	32	40	8	24	500
1-1/2	38	48	8	24	750
2	50	58	7	21	920
2	50	60	7	21	1050
2-1/2	63	73	6	18	1300
3	75	85	5	15	1650
3	75	87	5	15	1900
4	100	112	5	15	2900
4	100	114	5	15	3200
4	100	116	6	18	3700
5	125	137	4	12	3600
5	125	141	4	12	4000
6	152	170	4	12	7200
6	152	174	5	15	8000
8	200	216	3	9	6700

Length:≤30m

WORKING TEMPERATURE:

From -15 $^{\circ}$ C To + 75 $^{\circ}$ C

CHARACTERISTIC:

Excellent Flexibility, Crush And Abrasion Resistant, Smooth Tube For Less Friction Loss, Smooth Cover Allows Easy Dragging, Weathering Resistant, Clear To Have Full Visual Flow Of Materials, Corrosion Resistant To Light Chemicals, Various Lengths Available And Can Be Supplied With Different Couplings And Clamps.



RIBBED TYPE

Hose Nominal	Si I.D.	ze O.D.	MAX. W.P.	MAX. B.P.	Weight
Dimension (inch)	(mm)	(mm)	(bar at	: 23℃)	(g/metre)
3/4	19	23	6	18	230
1	25	29	6	18	290
1-1/4	32	36	6	18	350
1-1/4	32	38	6	18	400
1-1/2	38	44	6	18	550
1-1/2	38	46	6	18	650
2	50	54	5	15	550
2	50	56	5	15	700
2-1/2	63	69	4	12	880
2-1/2	63	71	4	12	1170
3	75	81	3	9	1160
3	75	83	3	9	1300
4	100	108	3	9	1950
4	100	110	3	9	2300
5	125	135	3	9	2300
5	125	137	3	9	3300
6	152	164	2	6	4500
6	152	166	2	6	5500
8	200	214	2	6	6300

PVC STEEL WIRE REINFORCED HOSE

-t- \$260















Chemical

APPLICATIONS:

The Hose Is Widely Used For Drawing And Conveying Water, Oil & Powder In Factories, Agriculture, Engineering, Foodstuffs And Sanitation Lines.

WORKING TEMPERATURE:

From -5 $^{\circ}$ C To + 65 $^{\circ}$ C


CHARACTERISTIC:

This Hose, With Steel Wire Screwing Inlaid In The Hose, Is Light, Transparent, With Small Bending Radius. It Has Good Adaptability To Hard Weather Conditions And Minus Pressure. With Colorful Symbol Lines On The Surface Of The Hose, It Can Be More Beautiful.

The regular specification of PVC spiral steel wire reinforced hose

Hose Nominal	Size(mm)		Pressure(MPa)		Length	Weight	Volume	Hose Nominal	Size(mm)		Pressure(MPa)		Length	Weight	Volume
Dimension (inch)	I.D.	O.D.	W.P	B.P	(m)	(kg/roll)	(m³)	Dimension (inch)	I.D.	O.D.	W.P	B.P	(m)	(kg/roll)	(m³)
5/16"	8	14	0.8	2	100	18	0.03	2"	50	57	0.4	1.1	50	50	0.307
3/8"	9	15	0.8	2	100	18.5	0.037		50	58	0.4	1.1	50	55	0.31
1/2"	12	18	0.6	1.8	100	22	0.051		50	59.6	0.4	1.1	50	60	0.31
5/8"	15	22	0.6	1.8	100	30	0.084		50	62	0.4	1.1	50	80	0.33
3/4"	19	26	0.5	1.5	50	17.5	0.063	2-1/2"	64	70	0.4	1.1	30	36	0.331
	20	24.6	0.5	1.5	50	12.5	0.076		64	72.4	0.4	1.1	30	42	0.331
	20	25.4	0.5	1.5	50	15	0.076		64	73.5	0.4	1.1	30	48	0.331
1"	25	29	0.5	1.5	50	12.5	0.085		64	74	0.4	1.1	30	54	0.331
	25	29.4	0.5	1.5	50	15	0.085		64	80	0.4	1.1	30	84	0.335
	25	31.6	0.5	1.5	50	20	0.089	3"	75	81.8	0.3	0.8	30	42	0.375
	25	31.8	0.5	1.5	50	25	0.089		75	82.4	0.3	0.8	30	48	0.375
	25	33	0.5	1.5	50	27	0.098		75	83.6	0.3	0.8	30	54	0.375
1-1/4"	32	36.6	0.5	1.5	50	20	0.129		75	85	0.3	0.8	30	60	0.421
	32	37	0.5	1.5	50	25	0.129		75	85.8	0.3	8.0	30	66	0.463
	32	40.2	0.4	1.1	50	32.5	0.166		75	92	0.3	0.8	30	105	0.47
	32	41	0.4	1.1	50	38	0.166	3-1/2"	89	100	0.3	0.8	30	75	0.547
1-1/2"	38	42	0.4	1.1	50	20	0.224	4"	102	110	0.3	8.0	30	75	0.703
	38	42.8	0.4	1.1	50	25	0.224		102	110.8	0.3	8.0	30	81	0.599
	38	44.6	0.4	1.1	50	35	0.224		102	112	0.3	8.0	30	90	0.599
	38	46	0.4	1.1	50	45	0.231		102	114.2	0.3	8.0	30	105	0.613
	38	48	0.4	1.1	50	52.5	0.231		102	114.6	0.3	8.0	30	120	0.627
1-3/4"	45	52.8	0.4	1.1	50	40	0.243		102	120	0.3	8.0	30	144	0.63
	45	53	0.4	1.1	50	50	0.271		102	121.6	0.3	8.0	30	150	0.641
1-7/8"	48	57.8	0.4	1.1	50	55	0.289		108	118	0.3	8.0	30	96	0.615
2"	50	56	0.4	1.1	50	35	0.307		108	120	0.3	8.0	30	105	0.616
	50	56.4	0.4	1.1	50	40	0.307	5"	127	141	0.2	0.6	20	100	0.892
	50	56.8	0.4	1.1	50	45	0.307	6"	152	166	0.2	0.6	20	130	1.243

PVC FIBER & STEEL WIRE REINFORCED HOSE



PVC Reinforcement PVC Inner Layer

APPLICATIONS:

The Hose Is Available For Transporting Liquid, Gas And Powder Under High Working Pressure

WORKING TEMPERATURE:

From -5 $^{\circ}$ C To + 65 $^{\circ}$ C

CHARACTERISTIC:

This Hose Is Made With Steel Wire Screwing
Inlaid In The Hoses, And High Quality Fiber
Reinforced By Advanced Technology, Can
Keep Its Shape And Working Normally Under
High Pressure As Well As Minus Pressure
Conditions. By Adding Colorful Symbol Lines
On The Surface Of The Hoses, That Looked
More Beautiful

The regular specification of PVC fiber and steel wire reinforced hose

	Hose Nominal	Size(mm)	Pressur	e(MPa)	Length	Weight	Volume
	Dimension (inch)	I.D.	O.D.	W.P	B.P	(m)	(kg/roll)	(m³)
	1	25	32	0.1~0.8	2.5	50	24	0.087
	1-1/4	32	40	0.1~0.8	2.3	40	28	0.19
	1-1/2	38	47	0.1~0.7	2.2	40	36	0.181
	2	50	61	0.1~0.7	2	40	57.5	0.26
	2-1/2	64	78	0.1~0.7	2	20	47.3	0.24
	3	75	90	0.1~0.6	1.8	20	58.3	0.447
	3-1/2	90	106	0.1~0.5	1.5	20	74	0.494
	4	100	116	0.1~0.5	1.5	20	82	0.476

LENGTH

20m to 100m Popular sizes: 20m 25m 50m 100m 25 to 300feet Popular sizes: 75' 100' 200' 300'

COLOR

Clear, White, Blue, Red, Orange, etc

PACKAGE

Be able to pack with shrink flim + Color label + Carton or as per buyer's request

MOQ

Mixed 1x20' container / 5000m per size







— 20

- 19 -

SPARY GUN





pcs/ctn:48 carton Size/cm: 48*32*33 n.w/g.w.:13.5/14.2KG GD-SP7206 Adjustable metal spray gun





GD-SP7205D Adjustable metal spray gun chrome plated



Adjustable Metal Spray Gun Chrome Plated

Size(HxL): 20*11.5cm packing:Blister card pcs/ctn:48 carton Size/cm: 49*46*18 n.w/g.w.:8.5/9.5KG GD-SP7207D 8-Pattern Metal Spray Gun Chrome Plated

8-pattern metal spray gun





7-pattern Soft coated round handle spray gun



carton Size/cm: 57*54*34 n.w/g.w.:13.6/15KG GD-SP7222 7-Pattern soft coated spray gun

Size(HxL): 22*11.5cm

packing:Blister card

pcs/ctn:48



GD-SP7208 Adjustable plastic spray gun



5-pattern plastic spray gun



Simple metal spray gun with soft handle



GD-SP7210 Plastic shower spray gun



Adjustable soft coated spray gun



GD-SP7216 7-Pattern soft coated spray gun



GD-SP7217 Adjustable plastic spray gun



GD-SP7218 7-Pattern plastic spray gun



Shower plastic spray gun



GD-SP7502 8-pattern plastic spray gun set









GD-SP7506 pcs/ctn:48 Adjustable metal spray gun set

WATER WANDS



SPRINKLER



LXH

GD-SR8106

Three arm sprinkler

with metal spike

11.5x29.5

L X H 11.5x28.5

GD-SR8105D

with metal spike

Metal impulse sprinkler

HOSE CART & REEL



GD-HC3101 Store up to 60mx1/2"hose



GD-HC3501 Store up to 60mx1/2"hose



GD-HC3301 Store up to 45mx1/2"hose



GD-HC3701 Store up to 45mx1/2"hose



GD-HC3201 Store up to 60mx1/2"hose



GD-HC3601 Store up to 60mx1/2"hose



GD-HC3401 Store up to 45mx1/2"hose



GD-HC3801 Store up to 45mx1/2"hose



GD-HC3004
Hanging rotatable hose reel store up to 15mx1/2" expandhose able



HOSE CONNECTOR



GD-HF5809E 1/2" Hose connector soft coated



GD-HF5819E 3/4" Hose connector soft coated



GD-HF5809EP 1/2" Soft coated hose connector with lock



GD-HF5819EP 3/4" Soft coated hose connector with lock



GD-HF5808E 1/2" Hose mender soft coated



GD-HF5810E 1/2" Water-stop hose connector soft coated



GD-HF5820E 3/4" Hose connector soft coated with water-stop



GD-HF5810EP
1/2" Soft coated water-stop
hose connector with lock



GD-HF5820EP 3/4" Soft coated water-stop hose connector with lock



GD-HF5818E 3/4" Hose mender soft coated



GD-HF5809EZ 1/2" Metal cap luxury hose connector soft coated



GD-HF5819EZ 3/4" Metal cap luxury hose connector soft coated



GD-HF5808Z 1/2" Zinc hose mender



GD-HF5809E-1 1/2" Coated hose connector



GD-HF5819E-1 3/4" Coated hose connector



GD-HF5810EZ

1/2" Metal cap luxury hose connector with water-stop



GD-HF5820EZ
3/4" Metal cap luxury hose



GD-HF5818Z 3/4" Zinc hose mender



GD-HF5810E-1 1/2" Coated hose connector with water-stop



GD-HF5820E-1 3/4" Soft coated hose connector with water-stop



GD-HF5809M 3/4" Male quick hose connector



GD-HF5812E 1/2"&3/4" Tap adaptor soft coated



GD-HF5805E 3/4" Tap adaptor soft coated



GD-HF5808E 1/2"&3/4" Hose mender soft coated



GD-HF5709 Small head 3/8" hose connector

HOSE CONNECTOR



GD-HF5809F 3/4" Female quick hose connector



GD-HF5807E 3/4"&1" Tap adaptor soft coated



GD-HF5811E 1" Tap adaptor soft coated



1/2"&3/4"&1" Soft coated

tap adaptor

GD-HF5709E Small head 3/8" Hose connector soft coated



GD-HF5808 1/2" Hose mender



HOSE CONNECTOR

GD-HF5817 1/2"&3/4"&1" Tap adaptor



GD-HF5812 1/2"&3/4" Tap adaptor 3/4" Tap adaptor



GD-HF5804 Two way hose coupling



GD-HF5809 1/2" Hose connector



3/4" Hose connector



GD-HF5821 Flexible tap adaptor, with 1/2"&3/4"&1" tap adaptor



GD-HF7201 Adjustable hose nozzle



GD-5003E 1/2"&5/8" Hose connector with control valve





3/4" Male adaptor



GD-HF5807 3/4"&1" Tap adaptor



GD-HF5811 1" Tap adaptor



GD-HF5803 Three way hose coupling



GD-HF5810 1/2" Water-stop hose connector



GD-HF5820 3/4" Water-stop hose connector



GD-HF5006E 1/2" Rotatory hose connector with lock



GD-HF7201E Adjustable hose nozzle soft coated



GD-HF5004E 1/2" Hose connector with control valve



GD-HF5839 1" Hose connector



GD-HF5505 1.75"to1.5"to1" Hose adaptor



GD-HF5504 1" Two way hose coupling



GD-HF5832 Big snap-in tap adaptor



GD-HF5812CP 1/2" Brass to 3/4" plastic



GD-HF5708 1/2"&3/4" Hose mender



GD-HF5719E 3/16" Soft coated hose connector



GD-HF5831 Screw-in tap adaptor



GD-HF5701 1/2" Male adaptor



GD-HF5002 Two way valve



3/4" Hose connector

GD-HF5911

big adaptor

3/4" Hose connector for



GD-HF5506 1" Female adaotor



GD-HF5501 1" Male adaptor



GD-HF5830 Snap-in tap adaptor



3/4" Brass to 1" plastic adaptor



GD-HF5010 Four way-valve



GD-HF5709ME 1/2" Hose connector soft coated with long head



GD-HF5001 One way hose coupling with side valve



GD-HF5705 1/2" Female tap adaptor



GD-HF5002-A Plastic with way valve 1" tap



GD-HF5601 Big adaptor with 3/4" male thread



GD-HF5903 Three way connector for big adaptor



GD-HF5904 Two way connector for big adaptor



GD-HF5907 3/4"&1" Tap for big adaptor

HOSE CONNECTOR



GD-HF5912 3/4" Water-stop hose connector for big adaptor



GD-HF7301 Adjustable hose nozzle with big adaptor



GD-HF5603 Three way big adaptor to normal size



GD-HF5604 Two way big adaptor to normal size



GD-HF5913 Hose basic set with big adaptor





HOSE CONNECTOR

1/2" Brass hose connector 1/2"&3/4" Brass tap adaptor 3/4" Brass hose connector 1/2" Brass hose mender





GD-HF5808C



GD-HF5805C 3/4" Brass tap adaptor



GD-HF5814FZ 1/2" Hose basic set with metal cap soft coated



GD-HF5816F 3/4" Hose basic set soft coated



GD-HF5814F 1/2" Hose basic set soft coated



GD-HF5814 1/2" Hose basic set



GD-HF5816 3/4" Hose basic set



GD-HF5810C 1/2" water-stop brass hose connector



GD-HF5807C 3/4"&1" Brass tap adaptor



GD-HF5820C 3/4 " water-stop brass hose connector



GD-HF5818C 3/4" Brass hose mender 1" Brass tap adaptor



GD-HF5811C



GD-HF5813FZ 1/2" Hose basic set with metal cap soft coated



GD-HF5815F 3/4" Hose basic set soft



GD-HF5813F 1/2" Hose basic set soft



GD-HF5813 1/2" Hose basic set



GD-HF5815 3/4" Hose basic set



GD-HF5804C Two way brass hose coupling



GD-HF7201C Adjustable brass hose nozzle



GD-HF5002C Brass two way with control valve



GD-HF5814C 1/2" Brass hose basic set



GD-HF5816C 3/4" Brass hose basic set



GD-HF7214 Simple metal spray gun



GD-HF203 2-Hour three way timer

CHARACTERISTIC:

• The Mechanical Timer Can Be Set Between 0-120mins, And With Three Outlets Which Can Be Automatic And Manual Control.



• The Digital Timer Is With Reliable Pre-Set Program, With Multi-Function To Set. And Easy To Use.







GD-HF9806

Brass air hose fitting



GD-HF5801C 3/4" Brass male adaptor



GD-HF5808Z 1/2" Zinc hose mender



GD-HF5813C 1/2" Brass hose basic set



GD-HF5815C 3/4" Brass hose basic set



GD-HF9802/9803 Brass Quick air hose fitting nickle plated



GD-HF9801/9804 Brass Quick air hose fitting



GD-HF9807 2-ways brass fitting



GD-HF9808 3-ways brass fitting

spray gun

GD-HF2809

Plastic Cr plated

CAM AND GROOVE COUPLINGS

















В





Item D



American type

Male N.P.T. ends

